

## 2 Nozzles Beautiful Appearance, Excellent Performance Bernet Brand BNT50KA Petrol Dispenser for Petrol Gas Station

Our Product Introduction

for more products please visit us on [fueldispensermachine.com](http://fueldispensermachine.com)

### Basic Information

- Place of Origin: Anhui China
- Brand Name: Bernet
- Certification: ISO9001.ATEX,UL,MID
- Model Number: BNT50KB
- Minimum Order Quantity: 2PCS
- Price: \$834.00-\$1598.00/pieces 10-100 pieces
- Packaging Details: 1PCS PER CARTON
- Delivery Time: 10-15days
- Payment Terms: L/C,T/T,Western Union,D/P
- Supply Ability: 100 Piece/Pieces per Month




### Product Specification

- Ambient Temperature: -40°C~+55°C
- Humidity: ≤95%
- Max Flow: 50L/min Or 80L/min
- Repeating Accuracy: ≤0.15%
- Inlet Vacuum: ≥54kpa
- Line: 1 To 2 Line
- Nozzle: 1 To 2
- Noise: ≤70dB(A Class)
- Single Package Size: 105X65X205 Cm
- Single Gross Weight: 180.000 Kg
- Name: Fuel Dispenser
- Highlight: **Bernet Brand Petrol Dispenser, Excellent Performance Petrol Dispenser, 2 Nozzles Petrol Dispenser**



### More Images



# Product Description

2 Nozzles Beautiful Appearance, Excellent Performance Bernet Brand BNT50KA Petrol Dispenser for Petrol Gas Station  
 Advanced Fuel Dispenser Specifications  
 The fuel dispenser is designed to meet the highest industry standards, ensuring reliable performance in various environments. Compatible with oil-based media, this fuel dispenser operates efficiently in ambient temperatures ranging from -40°C to +55°C and handles humidity levels up to 95%. With a maximum flow rate of 50L/min or 80L/min, the fuel dispenser delivers fuel quickly while maintaining precision, boasting a repeating accuracy of ≤0.15%. Equipped with an inlet vacuum of ≥54kPa, the fuel dispenser ensures smooth fuel delivery with minimal disruptions. Noise levels are kept below 70dB (A class), making it suitable for urban and residential areas. The fuel dispenser supports a single measurement range from 1 to 9900.00, catering to diverse fueling needs. Flexibility is a key feature of this fuel dispenser, offering 1 to 2 solenoid valves, 1 to 2 lines, and 1 to 2 nozzles for versatile applications. Whether for small-scale or high-volume operations, the fuel dispenser guarantees efficiency and accuracy. Built for durability and performance, this fuel dispenser is ideal for gas stations, fleet management, and industrial use. Its advanced technology ensures seamless operation, making the fuel dispenser a trusted choice worldwide. With robust construction and user-friendly features, the fuel dispenser sets a new benchmark in fuel dispensing technology. In summary, the fuel dispenser combines precision, reliability, and adaptability, making it an essential tool for modern fuel management. Choose the fuel dispenser for unmatched performance and longevity.

Product Parameters:

F e a t u r e s	F l o w r a t e O p t i o n s	Standard Flow (Gasoline/Diesel)	High Flow (Diesel)
	D e l i v e r y s p e e d	50L/min or 80L/min	50L/min or 80L/min
	M a r k e t A v a i l a b i l i t y	Middle East, Africa & South East Asia	Middle East, Africa & South East Asia
	A p p r o v a l s	ATEX, MID, OIML,SONCAP	
	F u e l C o m p a t i b i l i t y	Up to 10% Ethanol content & 5% Biodiesel content	

	M a x N u m b e r o f F u e l G r a d e s / M e t e r s	2 Grades / 2 Meters	
	H o s e M a n a g e m e n t	Easy Hose with Non-obstructing Money Volume Display View	
	P u m p S t o p ( o p t i o n )	√	√
	N o i s e L e v e l - 6 5 d B ( S u c t i o n M o d e l )	√	√

H y d r a u l i c O p t i o n s	M e t e r i n g U n i t	Bernet piston Meter with improved e-Calibration	Bernet piston Meter with improved e-Calibration
	P u l s a r	Option (Secure pulsar with lift-off detection )	Option (Secure pulsar with lift-off detection )
	M o t o r ( S u c t i o n M o d e l )	Standard: 1phase, 220-240 Vac   option : 3 Phase, 380 - 440 Vac	Standard: 1 phase, 220-240 Vac   option : 3 Phase, 380 - 440 Vac
	P u m p F i l t e r T y p e	Standard: Washable   Option: Replaceable	Standard: Washable   Option: Replaceable
	M e t e r F i l t e r T y p e	Standard: Washable   Option: Replaceable	Standard: Washable   Option: Replaceable
	P u m p i n g U n i t	Standard:Vane Option: Gear	Standard: Vane   Option: Gear

	D i s p l a y T e c h n o l o g y	High Contrast LCD Display with direct sunlight readability	High Contrast LCD Display with direct sunlight readability
E l e c t r o n i c O p t i o n s	D i s p l a y S i z e	Money :8 digits with floating decimals (99,999,999) 40 mm height	888888.88
		Volume :8 digits with floating decimals (9,999,999), 40 mm height	
		PpU : 6 digits with floating decimals (999,999), 25 mm height/option: 5 digits with floating decimals (999,999), 25 mm height	
	K e y p a d	Film keypad/option:stainless steel keypad	Film keypad/option:Stainless Steel keypad
	P o S C o n n e c t i v i t y	Bernet Wire Protocol   option: IFSF Protocol	
	E l e c t r o n i c S P o w e r S u p p l y	Single Phase, Standard: 90 Vac - 260Vac   Option: 90 Vac - 380Vac	

	T o t a l i z e r ( C u m u l a t i v e & D a i l y )	12 Digits (99gg999999.999)	
	Ti c k e t P r i n t e r ( O p t i o n )	√	√
	M o t o r O v e r - v o l t a g e P r o t e c t i o n	√	√

E l e c t r o n i c a l l y A d j u s t a b l e F l o w r a t e ( O p t i o n )	√	√
E l e c t r o m e c h a n i c a l T o t a l i z e r ( O p t i o n )	Enhanced Security EMT   7 digit Totalizer (9999999) with 1 Liter resolution	

What'sapp:+8619314084039      Gmail:bernet0006@gmail.com